



Kerr-Addison – Chesterville East Extension

Kerr-Addison – Chesterville East Extension as referenced in the news release dated September 21, 2026.

Table 1. Kerr-Addison – Chesterville East Extension Collars:

Hole ID	Easting	Northing	Elevation (masl)	Azimuth	Dip	Total Length (m)	Zone
KAD26-400	606355	5332902	316.4	356	-49	495	CVE Extension
KAD26-403	606300	5332854	327.0	355	-50	561	CVE Extension
KAD26-404	606424	5333012	315.6	343	-47	375	CVE Extension
KAD26-406	606465	5333072	302.0	358	-52	375	CVE Extension
KAD26-407	606424	5333012	315.6	342	-62	525	CVE Extension
KAD26-408 ³	606465	5333072	308.9	345	-61	81	CVE Extension
KAD26-408A	606465	5333072	302.0	341	-62	506	CVE Extension
KAD26-410 ³	606355	5332902	316.4	351	-53	64	CVE Extension
KAD26-410A	606355	5332902	316.4	351	-53	555	CVE Extension
KAD26-411	606465	5333072	302.0	328	-45	273	CVE Extension
KAD26-412	606465	5333072	302.0	325	-64	208	CVE Extension
KAD26-413	606424	5333012	315.6	346	-52	387	CVE Extension
KAD26-415	606465	5333072	302.0	330	-60	435	CVE Extension
KAD26-416	606355	5332902	316.4	341	-51	533	CVE Extension
KAD26-417 ³	606424	5333012	315.6	332	-48	48	CVE Extension
KAD26-417A	606424	5333012	315.6	332	-48	333	CVE Extension
KAD26-418	606355	5332902	316.4	341	-59	654	CVE Extension
KAD26-420	606563	5333390	318.9	153	-45	255	CVE Extension
KAD26-421	606424	5333012	315.6	330	-65	555	CVE Extension
KAD26-423A	606657	5333465	320.2	150	-45	315	CVE Extension
KAD26-424	606355	5332902	316.4	341	-56	558	CVE Extension
KAD26-425	606424	5333012	315.6	316	-53	384	CVE Extension
KAD26-426	606574	5333474	321.5	195	-51	465	CVE Extension
KAD26-429	606424	5333012	315.6	303	-51	402	CVE Extension
KAD26-430	606355	5332902	316.4	328	-56	522	CVE Extension
KAD26-431	606559	5333540	319.0	175	-63	645	CVE Extension
KAD26-432A	606300	5332854	327.0	319	-51	543	CVE Extension
KAD26-433	606424	5333012	315.6	314	-65	570	CVE Extension
KAD26-434	606355	5332902	316.4	316	-51	513	CVE Extension
KAD26-435	606559	5333540	319.0	196	-71	696	CVE Extension
KAD26-436	606424	5333012	315.6	314	-61	570	CVE Extension
KAD26-439	606355	5332902	316.4	317	-56	580	CVE Extension
KAD26-440	606559	5333540	319.0	156	-75	675	CVE Extension
KAD26-442	606424	5333012	316.4	328	-62	483	CVE Extension



Hole ID	Easting	Northing	Elevation (masl)	Azimuth	Dip	Total Length (m)	Zone
KAD26-443	606355	5332902	316.4	308	-46	474	CVE Extension
KAD26-445	606559	5333540	319.0	155	-48	462	CVE Extension
KAD26-447	606424	5333012	315.6	152	-59	285	CVE Extension
KAD26-448	606559	5333540	319.0	131	-64	591	CVE Extension
KAD26-450	606476	5333023	309.1	147	-45	291	CVE Extension
KAD26-451	606300	5332854	327.0	140	-46	600	CVE Extension
KAD26-453	606318	5333260	334.7	170	-64	593	CVE Extension
KAD26-454	606502	5333074	303.8	134	-62	224	CVE Extension
KAD26-457	606502	5333074	303.8	137	-45	192	CVE Extension
KAD26-461	606216	5333212	329.9	172	-45	534	CVE Extension
KAD26-473	606318	5333260	334.7	170	-45	459	CVE Extension
KAD26-474 ³	606278	5332945	332.6	323	-52	18	CVE Extension
KAD26-474A	606278	5332945	332.6	323	-52	348	CVE Extension
KAD26-475	606216	5333212	329.9	133	-45	423	CVE Extension
KAD26-477	606437	5332869	312.2	323	-70	792	CVE Extension
KAD26-480	606278	5332945	332.6	339	-52	342	CVE Extension
KAD26-484 ³	606216	5333212	329.9	170	-50	69	CVE Extension
KAD26-484A	606216	5333212	329.9	162	-52	549	CVE Extension
KAD26-485	606318	5333260	334.7	121	-64	517	CVE Extension
KAD26-488 ³	606278	5332945	332.6	350	-51	16	CVE Extension
KAD26-488A	606278	5332945	332.6	350	-51	363	CVE Extension
KAD26-491	606023	5333138	321.6	148	-57	657	CVE Extension
KAD26-492	606318	5333260	334.7	130	-47	432	CVE Extension
KAD26-494	606417	5333069	232.6	133	-49	252	CVE Extension
KAD26-496	606417	5333069	323.6	131	-64	446	CVE Extension
KAD26-501	606023	5333138	321.6	149	-63	723	CVE Extension
KAD26-503	606417	5333069	323.6	127	-73	336	CVE Extension
KAD26-505	606417	5333069	323.6	99	-60	312	CVE Extension
KAD26-507	606318	5333260	334.7	118	-73	600	CVE Extension
KAD26-509	606389	5332964	312.8	156	-61	174	CVE Extension
KAD26-517	606023	5333138	321.6	164	-55	402	CVE Extension
KAD26-518	606278	5333035	320.6	150	-56	237	CVE Extension
KAD26-522	606368	5333093	317.9	147	-50	288	CVE Extension
KAD26-527	606368	5333093	317.9	330	-47	165	CVE Extension

Notes on Table 1:

1. Table contains information for all 2026 diamond drill holes of the CVE program from the September 21, 2026 release.
2. Coordinate system NAD83 UTM Zone 17N.
3. Hole finished prematurely due to excessive deviation or downhole conditions preventing advancement.



Table 2. Kerr-Addison – Chesterville East Extension Drill Hole Assay Composites:

HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
KAD26-400	207.6	213.9	6.3	3.1	0.42
	221.3	221.8	0.6	0.3	0.29
	227.7	236.8	9.2	4.6	0.47
	242.0	245.4	3.5	1.8	0.34
	268.2	270.8	2.6	1.3	0.23
	301.0	301.7	0.7	0.4	0.32
	309.9	322.2	12.3	8.2	0.49
	362.3	369.5	7.2	4.8	1.72
	385.6	388.7	3.1	1.7	0.44
	434.4	435.4	1.0	0.6	0.33
	445.0	448.6	3.5	2.3	3.00
	467.2	468.2	1.0	0.6	0.33
KAD26-403	1.6	2.6	1.0	0.5	0.45
	7.6	11.6	4.0	1.8	0.57
	16.1	20.5	4.4	2.0	0.40
	26.5	30.5	4.0	1.8	0.37
	46.5	47.5	1.0	0.5	0.21
	219.4	220.4	1.0	0.4	0.44
	228.0	230.0	2.0	0.9	0.23
	234.9	235.9	1.0	0.4	0.29
	239.9	261.8	22.0	13.2	0.61
	285.2	286.0	0.8	0.4	0.27
	292.3	301.5	9.3	4.2	0.32
	316.0	317.0	1.0	0.5	1.18
	341.0	348.3	7.3	3.4	0.27
	355.3	360.3	5.0	2.4	0.60
	363.3	366.7	3.3	1.6	0.66
	370.7	372.7	2.0	1.0	0.26
	394.7	395.7	1.0	0.5	0.87
	412.0	426.0	14.0	8.9	0.74
	441.6	442.6	1.0	0.5	0.38
	504.1	508.0	4.0	2.2	2.20
KAD26-404	9.0	10.5	1.5	0.8	0.33
	56.8	57.8	1.0	0.6	0.35
	60.8	61.8	1.0	0.6	0.40
	115.4	126.4	11.0	7.0	0.64
	133.4	144.4	11.0	6.9	0.52
	156.0	159.0	3.0	1.7	0.89
	183.3	184.3	1.0	0.6	0.21
	207.7	209.0	1.3	0.7	1.03
	240.0	241.0	1.0	0.6	0.20
	294.1	299.3	5.2	3.2	2.29
<i>Incl.</i>	296.1	297.1	1.0	0.6	5.80
KAD26-406	199.5	200.3	0.8	0.4	0.30
	312.5	315.1	2.6	1.2	1.39



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
KAD26-407	110.0	118.0	8.0	2.8	0.28
	123.0	124.0	1.0	0.3	0.25
	139.0	140.0	1.0	0.3	0.23
	149.0	153.0	4.0	1.4	0.51
	168.0	175.5	7.5	3.1	0.77
	283.0	287.0	4.0	1.5	0.63
	309.0	322.1	13.1	5.7	1.11
	338.0	343.0	5.0	1.9	0.20
	350.0	361.0	11.0	4.8	1.36
	368.0	369.0	1.0	0.4	0.21
	385.0	392.5	7.5	3.0	0.39
	475.5	477.0	1.5	0.6	0.72
KAD26-408	<i>Not Sampled</i>				
KAD26-408A	94.1	98.2	4.1	1.8	1.24
	102.0	107.0	5.0	1.7	0.57
	125.4	136.0	10.7	3.6	0.21
	144.0	147.2	3.2	1.1	0.38
	266.1	267.4	1.4	0.4	0.20
	276.7	277.7	1.0	0.3	0.32
	336.0	336.7	0.7	0.2	0.69
	460.6	467.2	6.5	2.5	0.63
KAD26-410	<i>no significant values</i>				
KAD26-410A <i>Incl.</i>	204.6	212.0	7.4	3.2	0.51
	237.0	237.7	0.7	0.3	0.66
	265.6	269.6	4.0	1.7	0.61
	281.0	283.0	2.0	0.9	0.31
	306.4	307.0	0.6	0.3	1.14
	322.0	324.0	2.0	0.9	0.63
	369.9	370.9	1.0	0.4	0.78
	376.6	402.6	26.0	15.9	1.08
	377.6	378.6	1.0	0.6	4.69
	424.7	433.0	8.3	5.4	0.88
	482.2	483.0	0.8	0.4	0.96
	491.8	496.5	4.7	2.3	0.99
	512.9	514.0	1.1	0.5	0.30
	521.0	523.6	2.6	1.2	0.53
KAD26-411	50.1	51.8	1.7	1.0	0.63
	63.0	64.0	1.0	0.6	1.40
	95.0	100.0	5.0	3.6	1.23
	225.8	227.0	1.3	0.9	0.20
	230.0	231.4	1.4	1.0	0.21
KAD26-412	93.2	94.0	0.9	0.3	0.24
	99.5	100.5	1.0	0.3	3.10
	139.0	146.0	7.0	2.5	0.22
	162.0	163.0	1.0	0.4	0.27
KAD26-413	108.0	109.0	1.0	0.5	0.37
	115.0	118.0	3.0	1.5	0.25



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
	127.0	129.0	2.0	1.0	0.38
	134.0	145.0	11.0	6.4	0.72
	154.0	156.0	2.0	1.0	0.76
	162.2	163.0	0.8	0.4	0.45
	180.0	184.0	4.0	2.1	0.63
	188.1	194.0	5.9	3.1	0.43
	200.0	204.0	4.0	2.1	0.71
	250.0	255.0	5.0	2.6	0.87
	328.2	332.9	4.7	2.7	1.28
KAD26-415	74.0	95.0	21.0	10.4	0.83
	214.3	216.0	1.7	0.7	0.34
	228.0	229.9	1.9	0.8	0.62
	236.6	250.0	13.5	5.8	0.57
	275.0	287.6	12.6	5.2	1.35
	<i>Incl.</i> 281.3	282.0	0.8	0.3	5.27
KAD26-416	102.0	103.0	1.0	0.5	0.54
	200.8	201.8	1.0	0.5	0.39
	205.8	216.0	10.2	5.4	0.48
	232.4	233.4	1.0	0.5	0.68
	273.0	274.0	1.0	0.5	0.36
	278.0	279.0	1.0	0.5	0.87
	329.4	332.0	2.6	1.6	2.34
	381.9	383.2	1.3	0.7	2.86
	436.3	443.6	7.3	4.5	1.25
	<i>Incl.</i> 437.3	438.3	1.0	0.6	5.34
	463.6	464.2	0.7	0.4	0.30
KAD26-417	<i>no significant values</i>				
KAD26-417A	115.7	121.7	6.0	3.6	0.97
	135.6	146.9	11.3	6.8	0.25
	151.7	153.7	2.0	1.2	0.79
	160.2	163.2	3.0	1.8	0.62
	167.2	176.7	9.6	5.9	0.44
	193.0	194.0	1.0	0.6	0.43
	276.2	287.2	11.0	6.0	0.63
	294.4	295.4	1.0	0.6	4.82
KAD26-418	101.7	102.2	0.5	0.2	0.70
	269.0	279.5	10.5	4.6	0.96
	326.0	327.0	1.0	0.4	0.27
	422.6	434.0	11.4	4.4	0.76
	439.0	441.0	2.0	0.8	0.30
	593.0	597.0	4.0	1.8	1.31
KAD26-420	101.1	104.0	2.9	2.3	0.52
KAD26-421	74.0	75.4	1.4	0.4	1.08
	140.0	141.0	1.0	0.3	0.37
	166.0	167.0	1.0	0.3	0.21
	172.0	177.0	5.0	1.7	0.73
	187.0	190.8	3.8	1.3	0.45



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
<i>Incl.</i>	207.5	208.5	1.0	0.3	0.25
	246.0	247.0	1.0	0.4	0.87
	298.1	299.0	0.9	0.3	0.25
	310.0	313.0	3.0	1.2	0.80
	323.0	332.8	9.8	4.3	1.24
	368.0	369.0	1.0	0.4	0.31
	381.0	387.0	6.0	2.5	0.79
	495.0	500.8	5.8	3.1	1.45
	499.0	499.5	0.5	0.3	7.01
	506.5	507.0	0.6	0.3	0.65
KAD26-423A	101.0	102.0	1.0	0.8	1.18
	269.0	270.0	1.0	0.8	0.56
KAD26-424	207.0	208.0	1.0	0.5	0.49
	214.1	219.0	4.9	2.8	1.49
	223.0	224.0	1.0	0.5	0.24
	232.0	233.0	1.0	0.5	0.36
	243.0	244.0	1.0	0.5	0.22
	247.5	248.3	0.8	0.4	0.27
	279.3	280.0	0.8	0.4	0.29
	285.0	286.1	1.1	0.6	0.43
	316.0	317.0	1.0	0.6	0.21
	330.0	333.0	3.0	1.7	1.17
	378.0	382.0	4.0	1.9	1.02
	387.8	389.8	2.1	1.0	0.44
	390.5	393.0	2.6	1.2	0.28
	401.0	402.0	1.0	0.5	0.58
	466.0	467.0	1.0	0.5	0.47
	471.0	474.0	3.0	1.5	1.15
KAD26-425	43.0	43.6	0.6	0.3	0.21
	78.0	79.0	1.0	0.5	0.33
	106.7	109.1	2.4	1.3	0.36
	122.5	127.0	4.5	2.5	0.48
	141.0	146.0	5.0	2.8	0.44
	184.0	185.0	1.0	0.6	0.23
	243.0	244.0	1.0	0.6	0.32
	265.0	266.0	1.0	0.6	0.57
KAD26-426	328.0	336.5	8.5	4.8	0.66
	271.3	272.8	1.5	0.7	0.47
	280.1	284.0	3.9	1.9	0.34
	288.0	292.2	4.2	3.4	1.22
KAD26-429	450.0	451.0	1.0	0.5	0.22
	60.3	60.9	0.6	0.3	0.23
	64.7	66.5	1.8	0.9	0.87
	83.3	92.0	8.7	4.5	0.41
	99.7	100.7	1.0	0.5	0.63
	110.5	113.3	2.7	1.4	1.70
	119.7	125.0	5.3	3.0	1.32

[illegible]



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
	410.6	411.4	0.8	0.3	0.20
	509.7	515.3	5.6	2.8	0.50
KAD26-434	170.8	177.0	6.3	3.4	0.33
	180.3	181.0	0.7	0.4	0.40
	183.0	184.5	1.5	0.8	0.29
	190.0	199.1	9.1	5.1	0.21
	225.0	229.4	4.4	2.9	2.24
	236.0	237.0	1.0	0.6	0.49
	247.0	248.0	1.0	0.6	0.31
	251.0	252.0	1.0	0.6	0.22
	258.0	260.0	2.0	1.2	0.41
	276.7	284.0	7.3	4.3	0.41
	372.0	373.0	1.0	0.6	0.37
	378.5	381.3	2.8	1.7	0.58
	472.0	473.0	1.0	0.7	0.95
KAD26-435	506.3	507.0	0.8	0.3	14.02
	515.3	516.0	0.7	0.3	0.38
	544.0	547.0	3.0	1.2	0.44
	552.0	553.0	1.0	0.4	0.21
	555.0	556.0	1.0	0.4	0.22
KAD26-436	153.0	158.8	5.8	2.4	0.28
	159.0	163.1	4.1	1.7	0.63
	170.0	178.0	8.0	3.4	1.09
	182.0	183.0	1.0	0.4	0.26
	187.0	188.0	1.0	0.4	0.45
	197.0	198.0	1.0	0.4	0.30
	209.7	211.0	1.3	0.6	0.37
	238.7	240.0	1.3	0.6	0.21
	254.5	255.2	0.7	0.3	0.33
	265.0	274.0	9.0	4.5	1.54
	<i>Incl.</i> 266.0	<i>267.0</i>	<i>1.0</i>	<i>0.5</i>	<i>5.93</i>
	339.0	352.2	13.2	5.2	1.53
	482.0	486.0	4.0	1.4	1.77
	<i>Incl.</i> 485.0	<i>486.0</i>	<i>1.0</i>	<i>0.3</i>	<i>5.84</i>
	490.0	494.5	4.5	1.7	0.41
	500.0	501.0	1.0	0.3	20.31
KAD26-439	185.0	186.0	1.0	0.5	1.64
	193.0	194.0	1.0	0.5	0.22
	203.0	204.0	1.0	0.5	0.57
	220.0	222.0	2.0	0.9	0.34
	228.0	234.6	6.6	3.1	0.37
	239.0	246.0	7.0	3.3	0.70
	256.0	258.0	2.0	0.9	0.23
	259.0	260.0	1.0	0.5	0.24
	336.0	342.7	6.7	3.3	0.20
	407.0	409.6	2.6	1.3	0.40
	413.0	417.0	4.0	2.1	0.41



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
	421.6	424.0	2.4	1.2	1.44
	438.0	440.0	2.0	1.0	0.72
	530.0	531.0	1.0	0.5	0.24
KAD26-440	540.0	547.0	7.0	3.8	0.25
	551.0	555.0	4.0	2.2	0.47
KAD26-442 <i>Incl.</i>	58.0	59.0	1.0	0.4	0.93
	139.0	140.2	1.2	0.4	0.23
	148.0	153.0	5.0	1.9	0.43
	156.0	157.5	1.5	0.6	0.23
	173.7	174.6	1.0	0.4	0.32
	179.0	181.0	2.0	0.8	0.46
	189.0	190.8	1.8	0.7	0.28
	194.4	204.2	9.8	3.9	0.41
	222.0	224.0	2.0	0.8	1.13
	233.0	237.8	4.8	2.0	0.78
	268.0	269.7	1.7	0.8	0.25
	311.8	340.5	28.8	14.4	1.50
	317.0	327.8	10.8	5.4	3.10
	355.0	358.0	3.0	1.5	0.58
	438.0	442.0	4.0	2.0	0.38
KAD26-443	165.7	168.9	3.1	1.9	0.77
	217.0	232.0	15.0	11.8	0.46
	349.4	352.3	2.9	2.0	0.21
KAD26-445	256.0	257.0	1.0	0.8	0.20
	258.4	259.3	0.9	0.7	0.25
	281.2	282.0	0.8	0.7	0.44
KAD26-447	154.1	154.7	0.6	0.4	0.32
KAD26-448	404.4	419.6	15.3	8.5	0.78
	570.0	571.0	1.0	0.6	0.46
KAD26-450	106.0	107.0	1.0	0.8	0.45
KAD26-451	5.6	15.0	9.4	7.1	0.52
	28.0	29.7	1.7	1.3	0.27
	57.7	58.5	0.8	0.6	0.89
	62.0	63.0	1.0	0.8	0.38
	72.0	73.0	1.0	0.8	0.68
	97.0	106.4	9.4	7.2	0.27
	121.5	122.2	0.7	0.5	0.38
	357.0	358.0	1.0	0.8	3.54
	548.0	549.0	1.0	0.8	0.70
KAD26-453	182.0	183.8	1.8	1.2	3.83
	232.0	233.3	1.3	0.7	0.81
	311.8	322.5	10.7	6.2	0.45
	329.0	330.0	1.0	0.6	1.38
	339.1	341.4	2.4	1.4	0.30
	343.9	345.0	1.1	0.7	0.26
	347.0	348.0	1.0	0.6	0.20
	358.4	361.0	2.6	1.5	0.60



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
	376.0	377.0	1.0	0.6	0.87
	385.2	390.0	4.8	2.9	0.50
	398.0	399.0	1.0	0.6	0.34
	401.2	402.0	0.8	0.5	0.25
	404.0	407.0	3.0	1.9	0.24
KAD26-454	16.0	19.0	3.0	1.7	0.22
	67.0	69.1	2.2	1.2	0.25
	84.9	85.4	0.5	0.3	0.50
	205.0	206.0	1.0	0.6	0.24
KAD26-457	8.2	9.0	0.8	0.6	0.24
	12.0	15.0	3.0	2.3	0.23
	78.0	82.0	4.0	3.1	0.51
	130.0	131.0	1.0	0.8	0.22
KAD26-461	138.0	139.0	1.0	0.7	0.46
	144.0	144.8	0.8	0.5	0.23
	150.0	152.0	2.0	1.4	0.69
	288.2	289.2	1.0	0.7	0.74
	295.8	300.0	4.2	3.1	0.67
	312.0	321.7	9.7	7.2	0.20
	334.0	341.0	7.0	4.9	0.33
	345.0	352.2	7.2	5.0	0.25
	366.5	367.5	1.0	0.7	0.31
KAD26-473	374.2	378.1	3.9	2.6	0.76
	123.5	124.0	0.5	0.4	0.24
	127.0	127.8	0.8	0.6	0.52
	192.0	201.0	9.0	7.5	2.44
	197.0	198.0	1.0	0.8	9.75
	207.0	210.7	3.7	2.8	0.88
	217.1	222.0	4.9	3.8	0.81
	226.0	227.0	1.0	0.8	0.45
	240.0	244.0	4.0	3.4	3.21
	240.0	241.0	1.0	0.8	10.41
KAD26-474	249.0	268.0	19.0	15.9	0.47
	427.5	437.0	9.5	7.9	0.21
KAD26-474	Not Sampled				
KAD26-474A	20.0	28.0	8.0	4.3	0.38
	33.6	34.1	0.5	0.3	1.44
	38.0	42.0	4.0	2.2	0.35
	60.9	65.0	4.1	2.5	2.02
	62.4	63.0	0.7	0.4	5.26
	107.0	108.0	1.0	0.5	0.65
	129.0	133.3	4.3	2.4	1.05
	149.1	162.3	13.2	7.4	1.04
	229.0	231.1	2.1	1.2	0.94
	278.4	285.2	6.8	3.9	0.64
KAD26-475	152.2	155.9	3.7	3.2	2.59
	197.0	199.0	2.0	1.7	0.84



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
<i>Incl.</i>	242.4	243.6	1.2	1.0	1.16
	252.0	253.0	1.0	0.8	0.23
	264.0	273.5	9.5	7.9	0.62
	287.0	295.9	8.9	7.5	1.32
	287.0	288.0	1.0	0.8	5.32
KAD26-477	58.7	60.7	2.1	0.5	0.32
	66.0	78.2	12.2	0.5	0.63
	84.0	85.0	1.0	0.2	0.30
	86.7	87.2	0.5	0.1	0.20
	499.0	501.0	2.0	1.3	4.03
	509.0	511.0	2.0	1.2	0.34
	529.0	535.5	6.5	4.3	0.68
<i>Incl.</i>	5.1	6.0	0.9	0.5	0.22
	21.0	36.0	15.0	9.7	1.42
	25.4	26.4	1.0	0.7	13.32
	42.0	48.8	6.8	3.6	0.33
	52.0	64.2	12.2	8.0	1.02
	123.0	129.9	6.9	3.7	0.50
	131.4	154.0	22.6	13.9	0.51
	286.2	289.4	3.2	1.9	0.27
	312.0	316.3	4.3	2.6	1.22
KAD26-484	<i>Not Sampled</i>				
KAD26-484A	132.2	133.0	0.8	0.6	0.21
	149.6	154.0	4.4	3.7	1.53
	191.0	192.0	1.0	0.8	0.20
	215.2	223.0	7.8	5.9	0.29
	255.0	256.0	1.0	0.8	0.86
	300.0	303.0	3.0	2.3	0.24
	318.0	330.0	12.0	9.4	0.29
	338.0	339.0	1.0	0.8	0.22
KAD26-485	167.8	172.4	4.6	2.8	1.12
	236.0	237.0	1.0	0.6	0.23
	333.5	334.2	0.7	0.5	0.33
	335.0	336.0	1.0	0.7	0.23
	354.0	355.0	1.0	0.7	0.30
	360.0	361.0	1.0	0.7	0.28
	430.6	432.7	2.2	1.5	0.47
KAD26-488	<i>Not Sampled</i>				
KAD26-488A	7.0	9.0	2.0	1.0	0.33
	20.5	22.0	1.5	0.7	0.21
	30.0	39.0	9.0	4.6	0.26
	45.0	46.8	1.8	0.9	0.63
	51.0	56.0	5.0	2.6	0.67
	61.6	64.5	2.9	1.5	0.51
	118.5	125.5	7.0	5.2	0.82
	128.0	140.0	12.0	8.9	0.81
	149.0	158.6	9.6	5.3	0.25



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
	273.0	277.0	4.0	2.3	0.94
	298.0	299.0	1.0	0.6	2.27
	303.0	304.0	1.0	0.6	1.35
KAD26-491	210.7	218.7	8.0	5.6	0.53
	230.3	232.0	1.7	1.2	0.54
	341.0	341.6	0.6	0.4	0.78
	346.8	348.0	1.2	0.9	0.21
	380.0	381.0	1.0	0.7	0.33
	388.9	392.0	3.1	2.3	0.53
	434.0	436.0	2.0	1.5	0.39
	452.0	453.0	1.0	0.7	0.62
	557.1	558.9	1.8	1.4	0.61
	565.0	565.9	0.9	0.7	0.24
KAD26-492	579.8	580.8	1.0	0.8	1.92
	114.7	116.6	1.9	1.5	1.92
	166.0	167.0	1.0	0.8	0.41
	186.4	187.0	0.6	0.5	0.48
	248.0	250.1	2.1	1.6	0.24
	257.0	257.8	0.7	0.6	0.22
	262.6	267.9	5.3	4.3	0.36
	324.5	325.5	1.0	0.8	0.24
	329.5	330.5	1.0	0.8	0.42
	337.3	340.2	2.8	2.4	0.41
KAD26-494	347.7	348.7	1.0	0.8	0.36
	414.3	421.3	7.0	6.1	0.32
	8.0	8.6	0.6	0.4	0.25
KAD26-496	171.9	172.9	1.0	0.8	0.25
	174.0	174.7	0.7	0.5	0.23
KAD26-501	169.0	170.3	1.3	0.7	0.22
	254.0	271.0	17.0	9.4	0.27
	277.7	283.0	5.3	2.9	0.92
	304.0	305.0	1.0	0.6	0.34
	309.8	310.6	0.8	0.5	0.28
	314.0	324.4	10.4	5.9	0.24
	329.4	330.8	1.3	0.8	0.65
	336.0	346.0	10.0	5.6	2.02
	349.0	350.0	1.0	0.6	0.20
	444.0	445.2	1.2	0.7	0.25
KAD26-503	533.3	534.3	1.0	0.7	0.33
	597.0	598.0	1.0	0.7	0.27
KAD26-505	619.0	620.0	1.0	0.7	0.22
	258.8	259.8	1.0	3.0	0.32
	268.4	272.4	4.0	1.7	0.28
	42.7	43.6	1.0	0.4	0.20
	165.5	167.6	2.1	1.1	1.05
	228.7	229.9	1.2	0.7	0.26
	282.0	284.0	2.0	1.1	0.28



HOLE	From (m)	To (m)	Downhole Interval (m)	ETW (m)	Au (g/t)
	298.0	299.0	1.0	0.6	0.20
KAD26-507 <i>Incl.</i>	189.0	191.9	2.8	1.6	0.81
	249.9	267.0	17.1	10.1	1.28
	333.0	334.0	1.0	0.7	0.29
	340.0	341.0	1.0	0.7	0.29
	375.0	376.0	1.0	0.7	0.44
	511.0	515.0	4.0	3.0	1.48
	511.0	512.0	1.0	0.8	5.22
	532.0	533.0	1.0	0.7	0.67
KAD26-509	<i>no significant values</i>				
KAD26-517	223.9	225.9	2.0	1.3	0.61
	255.0	260.9	5.9	4.0	0.45
	279.0	281.0	2.0	1.4	0.30
	285.0	289.3	4.3	3.0	0.21
	293.0	294.0	1.0	0.7	0.30
	350.0	351.0	1.0	0.7	0.31
KAD26-518	24.7	26.0	1.3	0.8	0.20
	85.0	89.6	4.6	3.0	0.61
	105.0	107.0	2.0	1.3	0.25
KAD26-522	31.8	32.5	0.8	0.5	0.29
	36.2	38.3	2.1	1.5	0.60
	52.0	56.0	4.0	2.9	0.46
KAD26-527	20.4	24.0	3.7	2.2	0.33
	31.0	37.0	6.0	4.0	1.22
	40.1	42.0	1.9	1.2	0.91
	52.0	53.0	1.0	0.6	0.22
	95.1	101.8	6.6	3.7	1.09

Notes on Table 2:

1. Estimated True Widths (ETW) are estimated based on drill hole Geology or comparison with other on-section drill holes.
2. The composite assay grades presented in the summary tables are calculated using a minimum average of 0.20 g/t for Au, with a maximum of 3.0 m internal waste and no grade capping.



Corporate Office

123 Front Street West, Suite 905
 Toronto, ON M5J 2M2



705-998-4392



contact@cadillacmines.com



www.cadillacmines.com



Project Office

1 Kerr Mine Road
 Virginiatown, ON P0K 1X0